

XMS-1010P

WHAT THIS PRODUCT DOES:

With 8 Gigabit PoE+ ports and 2 additional Gigabit ports, the Luxul 10 Port/8 PoE+ Gigabit Managed Switch (XMS-1010P) is an ideal solution for use with an 8 Channel NVR Security System. The 8 Gigabit PoE+ ports ensure that all 8 cameras can be connected while still offering 2 additional Gigabit ports for use as uplinks to your router, main switch, or even directly to the NVR. With a healthy budget of 130W and a max of 30W per port, you'll have sufficient power for even the most demanding projects. The XMS-1010P also offers powerful management features such as remote reboot of connected IP cameras, VLAN support and specific PoE management features that ensure optimal benefit from your network.

- ▶ Connect up to 8 IP Cameras or Other PoE-Enabled Devices (Max Output 130 Watts)
- ▶ Add 802.3af/at Gigabit PoE+ Capability to Your Network
- ▶ Remotely Manage and/or Reboot Your PoE-Enabled Devices
- ▶ Optimize Your Network with VLAN, QoS and PoE Management
- ▶ Simply Plug and Play

FEATURES:

- ▶ 10 Gigabit RJ45 802.3af/at PoE+ Ports
- ▶ 2 Gigabit RJ-45 uplink ports
- ▶ 130 Watt Power Budget
- ▶ 20Gbps Switching Capacity
- ▶ 802.1Q VLAN (with Trunking) and QoS Support
- ▶ Plug-and-Play Installation with Intuitive Management
- ▶ Simple Power Management of PoE-Enabled Devices
- ▶ Quiet Operation
- ▶ Flexible Mounting Options: Surface, Wall or Standard 19" Rack
- ▶ Three Year Limited Warranty

10 Port/8 PoE+ Gigabit Managed Switch



XMS-1010P TECHNICAL SPECIFICATIONS

Hardware Features	
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.3ab, IEEE 802.3af, IEEE 802.1D, IEEE 802.3x
Interface	<ul style="list-style-type: none"> ▶ RJ-45 <ul style="list-style-type: none"> ▶ 10 Base-T: Cat.5 UTP /STP ▶ 100 Base-TX: Cat.5 UTP /STP ▶ 1000Base-T: Cat.5, Cat.5e or Cat.6 UTP/STP ▶ Cable Recognition for Straight-through or Crossover Cables
LED	<ul style="list-style-type: none"> ▶ Per Unit: Power ▶ Per Port: Link/Activity, 1000mbps, PoE
Power	AC 100-240V, 50-60Hz input
Power Supply	External Power Adapter
Power Budget	130 Watts Maximum
VLAN	<ul style="list-style-type: none"> ▶ 802.1Q Max 4094 VIDs ▶ Port Based VLAN ▶ Supports 1 Management VLAN
Quality of Service (QoS)	<ul style="list-style-type: none"> ▶ 4 Queues per port ▶ Queue Handling: Strict, Weighted Round Robin (WRR) ▶ CoS Based on DCSP, 802.1P and Port-based Priority Queues ▶ Port-based Bandwidth Control
Network Data Transfer Rate	<ul style="list-style-type: none"> ▶ Ethernet: 10Mbps (Half-duplex) ▶ Ethernet: 20Mbps (Full-duplex) ▶ Fast Ethernet: 100Mbps (Half-duplex) ▶ Fast Ethernet: 200Mbps (Full-duplex) ▶ Gigabit Ethernet: 2000Mbps (Full-duplex)
Operating Temperature	32°F to 104°F (0°C to 40°C)
Operating Humidity	10% to 90% (Non-condensing)
Dimensions L xWxH in. (mm)	11.5"(292) x 7"(178) x 1.75"(44.5)
Weight lbs (kg)	3.9 (1.8)
Certification	FCC, IC, CE, RoHS, EN60950

All references to speed are for comparison purposes only. Product specifications, size and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

Warranty:

- ▶ 3 Year Limited Warranty

Minimum System Requirements

- ▶ Suitable Network/PoE Devices
- ▶ Ethernet Cable
- ▶ Internet Connection to View Documentation Online

Package Contents

- ▶ 10 Port/8 PoE+ Gigabit Managed Switch
- ▶ Rack Mount Kit
- ▶ Rubber Feet
- ▶ Power Cord
- ▶ Quick Install Guide