

PRELIMINARY

SB 10i ULTRA-COMPACT SUBWOOFER




Description	Ultra compact subwoofer: 1 x 10" amplified by LA2Xi / LA4X / LA8 / LA12X	
	Preset [SB10_100]	Preset [SB10_200]
Low frequency limit (-10 dB)	27 Hz	29 Hz
Maximum SPL^{1,2}	122 dB	124 dB
Nominal directivity	Standard	
Transducers	1 x 10" cone driver	
Acoustical load	Bass-reflex, L-Vents	
Nominal impedance	8 Ω	
Connectors	4-point terminal block with push-in connection and connector sealing plate	
Rigging and handling	8 x M6 inserts for external rigging kits in on-wall integration	
Weight (net)	15 kg / 33 lb	
Cabinet	Premium grade Baltic birch plywood	
Front	Coated steel grill Acoustically neutral 3D fabric	
Finish	Dark grey brown Pantone 426 C Pure white RAL 9010 Custom RAL code on special order	
IP	IP55	

¹ Peak level at 1 m under half space conditions using pink noise with crest factor 4 (preset specified in brackets).
² For Max SPL values using LA2Xi, refer to LA2Xi system specification sheet.

INTEGRATION




► SB10i on the ground




► SB10i on-wall integration

DIMENSIONS



Front



Bottom