

Unilumin LED Conference All-in-One Machine T1

Product Parameter Table

Specifications and Models		T1-108	T1-135	T1-162
Basic Parameters	Display Size (inch)	108	135	162
	Dot Spacing (mm)	1.25	1.5625	1.875
	Overall Dimensions (W/H) (mm)	2412x1386	3012x1724	3612x2061
	Screen Resolution (W×H)	1920x1080	1920x1080	1920x1080
	Maintenance Method	Full front maintenance	Full front maintenance	Full front maintenance
	Total weight (kg)	88	138	192
	Border Material/Color	Profile/Black	Profile/Black	Profile/Black
	Operating Voltage	AC 100 V ~ 240 V, 50/60Hz		
	Maximum Power Consumption (W)	1600	1500	1800
	Average Power Consumption (W)	480	450	540
	Installation Method	Wall Hanging, Mobile Bracket		
	Packaging Material	Wooden Box + Carton + Foam		
	Certification Type	CE/UL		
Display Parameters	Encapsulated Type	SMD1010	SMD1010	SMD1515
	Brightness of White Balance (cd/m ²)	400 (adjustable)	400 (adjustable)	400 (adjustable)
	Repetition Frequency (Hz)	50/60	50/60	50/60
	Refresh Rate (Hz)	3840	3840	3840
	Gray Scale (bit)	14	14	14
	Screen Contrast	5000:1	5000:1	5000:1
	Horizontal/vertical Viewing Angle (degrees)	160/160	160/160	160/140

Mainboard Parameters	Operating system	Standard Android 7.1
	Running Architecture	2*Cortex-A72 +4*Cortex-A53
	Memory/Storage	Standard 4G/16G
	Remote Control Operation	Support
Sound Parameters	Sound Brand	Yamaha
	Rated Power (W)	30
	Interface	HDMIx1 Input/HDMIx1 Output/Digital Fiber/HDMI ARC
	Surround	Supports DTS decoding, Dolby stereo panoramic surround
	Control	Support Sound Bar Controller software control/remote control/panel key operation